

TECHNICAL DATA SHEET

Ethylene Glycol 40/60

Technical · 40/60

CAS NUMBER	ALLIANCE CODE	GENERATED
107-21-1	SHOPIFY-8019745144874	2026-09-11
REVISION	REVIEWED	
1.1	2026-09-09	

IDENTITY & COMPOSITION

PRODUCT NAME	ALLIANCE CODE
Ethylene Glycol 40/60	SHOPIFY-8019745144874
GRADE	CONCENTRATION
Technical	40/60
CAS NUMBER	FORMULA
107-21-1 Adjudicated	C2H6O2 Adjudicated
MOLECULAR WEIGHT	PRODUCT TYPE
62.07 Adjudicated	mixture

SPECIFICATIONS

TEST	SPECIFICATION	TYPICAL	METHOD	SOURCE
Assay	39.0 – 41.0 %, by volume	40.0 %	—	Interpreted
Sulfate (SO4)	2.7 ppm max	0.21 ppm	Turbidimetric, ACS procedure	Interpreted
Heavy metals (as Pb)	0.43 ppm max	0.043 ppm	ICP-OES / ACS heavy metals procedure	Interpreted

TEST	SPECIFICATION	TYPICAL	METHOD	SOURCE
Acidity as Acetic Acid	0.0021% max	0.00013 %	—	Interpreted
Chloride (Cl)	0.44 ppm max	0.043 ppm	—	Interpreted
Diethylene Glycol	0.021% max	0.0085 %	—	Interpreted
Iron (Fe)	0.048 ppm max	0.0085 ppm	—	Interpreted
Residue after evaporation	0.0022% max	0.00043 %	—	Interpreted
Composition	40 % ethylene glycol / 60 % deionized water, by volume	Conforms	By formulation; confirmed by specific gravity	Interpreted
Freeze point	-12.6 °F (-24.8 °C) max	-12.6 °F (-24.8 °C)	ASTM D1177	Interpreted

Specification values are guaranteed limits. Typical values are representative of production lots and are not guaranteed. Lot-specific certificates of analysis ship with every order.

AVAILABLE GRADES SAME CAS, ALTERNATE GRADES AND CONCENTRATIONS

GRADE	CONCENTRATION	TYPICAL ASSAY	SKU
THIS GRADE Technical	40/60	—	current
Technical	60/40	—	ethylene-glycol-60-40
Laboratory	50/50	—	ethylene-glycol-50-50
Technical	29.98%	—	ethylene-glycol-30-70
ACS Grade	—	—	ethylene-glycol-acs-grade

Typical assay shown is the rolling-window mean from the sibling product's most recent lots. Grade selection drives downstream end-use — verify the sibling grade matches your specification before substitution.

PHYSICAL & CHEMICAL PROPERTIES

PROPERTY	VALUE	SOURCE
Appearance	Clear, colorless to pale liquid	Published reference
Color	10 max	Interpreted
Odor	Mild, characteristic	Published reference
pH	Essentially neutral (unbuffered blend)	Published reference
Specific Gravity (20 °C)	1.051 – 1.061	Interpreted
Density	1.055 g/mL at 20 °C	Published reference
Boiling Point	~104 °C	Published reference
Melting Point	–24 °C (freeze / crystallization onset)	Published reference
Flash Point	Not flammable (aqueous solution)	Published reference
Solubility (water)	Miscible with water	Published reference

REGULATORY & TRANSPORT

DOT / 49 CFR

UN NUMBER

Not regulated **Adjudicated**

PACKING GROUP

Not regulated **Adjudicated**

HAZARD CLASS

Not regulated **Adjudicated**

PROPER SHIPPING NAME

Not regulated **Adjudicated**

GHS / OSHA HAZCOM 2012

SIGNAL WORD

Warning **Adjudicated**

H-CODES (HAZARD STATEMENTS)

H302, H373 **Adjudicated**

P-CODES (PRECAUTIONARY STATEMENTS)

P260, P264, P270, P301+P312, P314, P330, P501

Adjudicated

OCCUPATIONAL EXPOSURE LIMITS

OSHA PEL (29 CFR 1910.1000)

— **no canonical**

ACGIH TLV

— **no canonical**

NIOSH REL

— **no canonical**

NIOSH IDLH

— **no canonical**

Transport descriptions reflect 49 CFR 172.101 lookup at time of publication. Sourced data: ECHA CLP Annex VI for harmonised classifications, NIOSH Pocket Guide for REL/IDLH, OSHA Z-Tables for PEL. Always verify against the latest regulatory text before shipment-critical decisions.

APPLICATION GUIDANCE

Ethylene Glycol 40/60 (Technical) is a glycol-based heat-transfer and freeze-protection fluid. Concentration sets the freeze and burst protection; the inhibitor package sets how long the system stays protected from corrosion.

- Closed-loop heat transfer and process cooling
- Data-centre and chilled-water freeze protection
- HVAC hydronic loops and glycol makeup
- Freeze and burst protection for idle or seasonal systems
- Humectant and carrier applications (USP/food-grade propylene glycol only)

Verify concentration against the required freeze and burst protection, and confirm elastomer and metallurgy compatibility for the service temperature. Ethylene glycol is toxic by ingestion and must not be used where incidental food or potable contact is possible — specify a propylene glycol grade for those services.

STORAGE & HANDLING

RECOMMENDED STORAGE

Cool, dry, well-ventilated area in tightly sealed original containers. Neat glycols are combustible liquids with high flash points (roughly 99–111 °C) and do not require a solvent store; aqueous blends will not sustain combustion. Protect inhibited coolants from contamination and from freezing below their stated protection point.

Class-level guidance — not product-specific; the SDS controls.

INCOMPATIBILITIES

Strong oxidizers, strong acids and strong bases. Galvanized (zinc) surfaces are attacked by many inhibited coolant packages. Verify elastomer and gasket compatibility for the service temperature; EPDM is standard for glycol/water service.

Class-level guidance — not product-specific; the SDS controls.

For full hazard, PPE, and emergency response guidance, refer to the Safety Data Sheet (SDS) for this product. The SDS controls in all cases where guidance differs.

HANDLING PRECAUTIONS

Chemical-resistant gloves and splash goggles. Ethylene glycol grades are toxic by ingestion and must be kept away from food, drink and animals; propylene glycol grades are not. Avoid contact with hot surfaces and hot process equipment. Inhibitor packages deplete in service — monitor rather than top up blindly.

Class-level guidance — not product-specific; the SDS controls.

SHELF LIFE

Consult Technical Services for product-specific shelf life

PACKAGING & LOGISTICS

SHIPPING DESCRIPTION (US DOT)

Not regulated for transport.

Confirm against shipping documents and carrier requirements before tender.

NMFC CLASS
55

REVISION HISTORY

VERSION	DATE	CHANGE	TRIGGER
1.1	2026-09-09	Canonical data updated: 15 fields changed via the provenance/adjudication pipeline. • unNumber · canonical change (coa.data_provenance / adjudication) • hazardClass · canonical change (coa.data_provenance / adjudication) • packingGroup · canonical change (coa.data_provenance / adjudication) • dotProperShippingName · canonical change (coa.data_provenance / adjudication) • signalWord · canonical change (coa.data_provenance / adjudication) • ghsClassification · canonical change (coa.data_provenance / adjudication) • hazard_h_codes · canonical change (coa.data_provenance / adjudication) • hazard_p_codes · canonical change (coa.data_provenance / adjudication) • physicalProperties · canonical change (coa.data_provenance / adjudication) • casNumber · canonical change (coa.data_provenance / adjudication) • formula · canonical change (coa.data_provenance / adjudication) • molecularWeight · canonical change (coa.data_provenance / adjudication) • hsCode · canonical change (coa.data_provenance / adjudication) • countryOfOrigin · canonical change (coa.data_provenance / adjudication) • dotSubsidiaryHazardClass · canonical change (coa.data_provenance / adjudication)	canonical_change

This Technical Data Sheet is provided for technical reference. The Safety Data Sheet (SDS) controls in all cases where guidance differs. Values reflect Alliance Chemical canonical data at time of generation; subsequent revisions are recorded in the Revision History above.